

FLEET DASHCAMS + SECURITY SOLUTIONS

THE D-TEG DIFFERENCE

Dual Channel, Tamper Proof Drive Recorder

NEW Security
features **STOP
TAMPERING**



Vision solutions for superior
safety, productivity + security

SPECIFICATIONS

Image sensor	1/3" 2MP CMOS Digital Sensor
Angle of View	129° (horizontal: 107° , vertical: 55.7°)
Video	Built in camera: 1280x 720 (720P), 2nd camera optional, H.264
Audio	Built in omni-directional microphone, G.711
Recording Mode	Normal (continuous), Event (Shock Sensor, Panic), Dual (Cont. & Event)
Recording Time	8GB: 7.3 hrs, 32GB: 29.3 hrs w/ 2 cameras, normal quality, 15 FPS, HD
G-Sensor	Internal 3-dimension high sensitivity Bosch Gravity Sensor
GPS/ GLONASS	External (in the device mount), 10Hz
Storage Media	Max 64 GB (2 X SD/SDHC flash memory card slots)
Real Time Clock	Internal rechargeable battery
Back-up power	Super Capacitor to minimize data loss
LED	4 LED (Record, Network, Traffic light1, Traffic light2) + 1 LED (Parking)
Size & Weight	110 mm X 57 Ø , 150g
Data Access	Unique PC Viewer Program (playback, print, back up, and file conversion), Google Ear th Licensed
Power Input	DC 5V (Adaptor: Inputs 12V ~ 24V, Output 5V, 3A)
Power Use	Min 7.5W
Digital I/O	Max 4 inputs, 7 car signal inputs, and 4 outputs
Operation Temp.	-10°C ~ 60°C
Telecom	USB modem (optional), server connection, email, or SMS
Security Features	Key Lock Case to protect data and telecommunication (optional)



FEATURES:

Compact Windscreen Mounted, 2 Channel MVDR

Hardwired Option – records whenever vehicle is running

Locking Cover – protects recorded information from tampering

Two Cameras – add a camera to record driver, load or rear view

Twin Data Storage – up to 64GB recording capacity

Network Connection – USB port available for 3G/4G dongle

**Geographically monitored surveillance
+ incident management solutions**



1800 728 226
1800 REV CAM

sales@truckrearvision.com.au
truckrearvision.com.au